





Assembling and the using the kayak

- Assembly area should be free of sharp rocks / stones
- Remove any mud or sand inside the boat and around the air inlet valves before you start assembling
- Inflate both side balloons / tubes equally
- Foot pump - inflate till the pump pressure is hard. If using another pump, the max pressure is 0.25 bar
- Do not leave the kayak under the sun for long periods

Storage and maintenance of the kayak

After paddling, ensure that the frame and skin is clean and dry before packing. If used on salt water, rinse the complete kayak with fresh water. For long term storage, it is recommended that the kayak is 100% dry and stored indoors in dry conditions, off cold concrete floors.

Skin repair instructions can be found on www.neriskayaks.com FAQ

Manufacturer's Warrantee

NERIS Ltd. The manufacturer guarantees kayak suitability and material quality under the condition that the assembly and storage instructions listed above have been followed. The manufacturing company will repair free within 36 months of use from the date of purchase should there be any manufacturing defects.

You can address any repair issues yourself as a result of external damage or incorrect assembly during the warrantee period and later. However, the kayak owner will take responsibility of all repair costs.

Contact us

Contact NERIS Ltd. regarding any queries not covered in this instruction manual.

KAYAK SERIAL NUMBER / СЕРИЙНЫЙ НОМЕР ИЗДЕЛИЯ:

DATE MANUFACTURED / ДАТА ПРОИЗВОДСТВА:

MANAGING DIRECTOR OF NERIS LTD / ДИРЕКТОР:

KONSTANTIN ABRAMOV